

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Leth Corp.</i>		Lease <i>Gushwa DR</i>		Well # <i>2</i>	
Location of Well	Unit <i>1650 N 2310 W</i>	Section <i>35</i>	Township <i>18</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor <i>Verna Drilling Co.</i>		Type of Equipment <i>Rotary to start 10-29-77</i>			

APPROVED CASING PROGRAM

* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>15"</i>	<i>10 3/4</i>	<i>32.75</i>		<i>380</i>	<i>200 cwt.</i>
* <i>9 1/2</i>	<i>7"</i>	<i>20</i>		<i>1150</i>	<i>500 "</i>
<i>6 1/8</i>	<i>4 1/2 + 5 1/2</i>	<i>9.5 + 14</i>		<i>2400</i>	<i>175 "</i>

Casing Data:

Surface *29* joints of *7"* inch *2.3* # Grade *API New J-55*

(Approved) (Rejected)

Inspected by *Levin Gorman* date *11-2-77*

Cementing Program

Size of hole *9 1/2"* Size of Casing *7"* Sacks cement required *400/5x*

Type of Shoe used *No. 1* Float collar used *Top & Btm 2 jts welded Thread-Lock*

TD of hole *1130' KD* Set *1117' 6"* Feet of *7"* Inch *2.3* # Grade *J-55*

New-used csg. @ *1117' 6"* with *150* sacks neat cement around shoe @ *155 c 2 1/2*