

RECEIVED

C:SF

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

JAN 23 1980

O. C. D.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☒

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

below.) 1980' FNL x 1650' FEL, Sec. 3

AT SURFACE: (Unit G, SW/4 SE/4)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐☒FRACTURE TREAT ☐☐SHOOT OR ACIDIZE ☐☐REPAIR WELL ☐☐PULL OR ALTER CASING ☐☐MULTIPLE COMPLETE ☐☐CHANGE ZONES ☐☐ABANDON* ☐☐(other) ☐☐

5. LEASE

LC-065478-b

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal F Gas Com.

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Und. Scoggin Draw Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA

3-18-27

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3560.1 GR

(NOTE: Report results of multiple completion or zone
change on Form 9-330.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a TD of 9392' and ran DST #1 9320'-9392'. Drilled to a TD of 9957' and ran 5-1/2" casing set at 9957'. Cemented with 875 sx Trinity Lite cement with 3/4% CFR-2 and 1/4# Flocele/sx and 270 sx Class H cement with 3/4% CFR-2 and 5# Potassium Chloride/sx. Plugged down 12:00 noon 1-6-80. Top of cement at approx. 3490'. Will test casing when move in completion unit.

DST Attached.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Bob Davis

TITLE

Assist. Admin. Ana

DATE

1-18-80

(This space for Federal or State office use)

APPROVED BY

GEORGE H. STEWART

TITLE

MANAGER

DATE

JAN 22 1980

CONDITIONS OF APPROVAL, IF ANY:

0+4 USGS-A, 1-Hou, 1-Susp, 1-BD, 1-Hondo