

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons DIVISION

Budget Bureau No. 1004-0135

811 S. 1st Street

Expires: March 31, 1993

Artesia, NM 88210-2834

File Number and Serial No.

## SUNDRY NOTICES AND REPORTS ON WELLS

NM-14842

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Travis Bassett-Birney #1

9. API Well No.

30-015-22370

10. Field and Pool, or Exploratory Area

Empire South Morrow

11. County or Parish, State

Eddy County, NM

## SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvey E. Yates Company

3. Address and Telephone No.

P.O. Box 1933, Roswell, NM 88202

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit J, 1980' FSL &amp; 1980' FEL

Sec 7, T18S, R29E

12 CHECK APPROPRIATE BOX (S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

- ☒ Notice of Intent
- ☐ Subsequent Report
- ☐ Final Abandonment Notice

## TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other Plug & Abandon
- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If wells directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PBTD: 10,875

TOC: 5 1/2" csg. TOC @ 7,950'.

PERFS: 10,754-10,760' (2 spf).

SURFACE CASING: 13 3/8" set @ 416'.

INTERMEDIATE CASING: 8 5/8" set @ 2,900'.

- 1) Set CIBP @ 10,664' w/35' cement on top.
- 2) Cut and lay down approximately 7,900' of casing. Load hole with 9# mud.
- 3) Set 100' plug (50' in/50' outside of 5 1/2" casing stub). Tag plug.
- 4) Set 300' plug @ 5,000'. Tag plug.
- 5) Set 100' plug @ 2,950'.
- 6) Set 150' plug @ 491'.
- 7) Set 20 sxs cement surface plug.

14. I hereby certify that the foregoing is true and correct

Signed

Dianna Rodgers

Title Production Analyst

Date

22-Aug-00

(This space for Federal or State office use)

(ORIG. SGD.) GARY GOURLEY

PETROLEUM ENGINEER

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instructions on Reverse Side