

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other instructions
verse side)E*
re-Form approved.
Budget Bureau No. 42-R1421.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0487738

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "AB" Com

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 30-18S-25E
Unit B NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

MAR 20 1978

2. NAME OF OPERATOR

Yates Petroleum Corporation

O. C. C.
ARTESIA, OFFICE

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' FNL & 1980' FEL of Sec. 30-18S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3617' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run Prod. Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8800'. Ran 5½" casing as follows: 67 jts of 5½" 17# K-55 (2194') 151 jts 15.5# K-55 (6280'), 10 jts of 17# K-55 (326') (Total 8800') set 8800'. 1-Guide shoe at 8800', Diff-Fill collar at 8767'. 6 centralizers. Cemented as follows: 250 gallons mud flush, 270 sacks of Howco Lite 6/10% CFR-2, 5#/sx KCL tailed in w/125 sacks of Class H 6/10% CFR-2, 5#/sx KCL. PD 4:00 PM 3-7-78. WOC. Ran Temperature Survey and found top of cement at 6600'. Pressure tested casing to 1500#. OK.

TD 8800'- PBTD 8767' - WIH w/Tubing Conveyed Gun, 2-7/8" tubing at 8525' and Guiberson Unit VI packer at 8526'. Perforated 8570-8590' w/80 .32" shots (4spf). GTS 2" - 918# on 3/4" choke = 13.3 MMCFPD. SITP 2500#.

RECEIVED

MAR 14 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Christine J. Johnson TITLE Geol. SectyDATE 3-14-78

(This space for Federal or State office use)

APPROVED BY Lee S. LoraTITLE ACTING DISTRICT ENGINEERDATE MAR 17 1978

CONDITIONS OF APPROVAL, IF ANY: