

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660 FNL, 1980 FEL, Sec. 30-18S-25E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☒
☐
☐
☐
☐
☒
☐

RECEIVED
OCT 29 1981

5. LEASE
NM 0487738

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal AB Com

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Wildcat Strawn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit B, Sec. 30-18S-25E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3617' GR; 3630' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rigged up pulling unit & pulled packer & tubing.

10-1-81 - Set CIBP at 8550'. Dumped 35' of cement on top of CIBP.

10-2-81 - WH & perforated 8235-8242' (Strawn) w/14 .50" holes. Set packer at 8207'. Acidized well w/1500 gallons 15% DS-30 acid & nitrogen plus ball sealers. Swabbed well w/show of gas.

10-16-81 - Frac'd perforations 8235-8242' w/1000 gallons 15% DS-30 Spearhead acid, 15000 gallons gelled fluid & CO₂, 38000# sand (5000# 100 mesh & 33000# 20/40 sand).

10-17-19-81 - Swabbed well.

10-22-81 - Well stabilized at 80 psi on 3/8" choke = 275 mcf/d.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James H. Miller TITLE Engineering Secty DATE 10-26-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NOV 13 1981
O.G.L.
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO