

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gulf oil Corp.</u>		Lease <u>Eddy & X State Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>8605 2310 E</u>	Section <u>18</u>	Township <u>18</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	Type of Equipment <u>Rotary</u>				
<u>APPROVED CASING PROGRAM</u>					
<u>*Witness</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8"</u>	<u>48</u>		<u>300</u>	<u>Circ</u>
<u>12 1/4</u>	<u>8 5/8"</u>	<u>24</u>		<u>1200</u>	<u>Circ</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.5 + 17</u>		<u>8700</u>	<u>500</u>
Casing Data:					
<u>Surface</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>K-55</u>					
(Approved) (Rejected)					
Inspected by <u>M.S.</u> date <u>4/10/78</u>					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required <u>1000</u>					
Type of Shoe used <u>guide</u> Float collar used <u>invert</u> Btm & jts welded <u>yes</u>					
TD of hole <u>1221'</u> Set <u>1221'</u> Feet of <u>8 5/8</u> inch <u>24</u> # Grade <u>K-55</u>					
New-used csg. @ <u>1221'</u> with <u>200</u> sacks neat cement around shoe					
+ <u>200</u> sack <u>thin set</u> additives <u>29 cc. 29 cc.</u>					
Plug down @ <u>6045</u> (AM) (PM) Date <u>4/11/78</u>					
Cement circulated <u>yes</u> No. of Sacks <u>125</u>					
Cemented by <u>BJ</u> Witnessed by <u>Mike Stutts</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>+600 sks BJ light</u> <u>2 Baskets @ 655' + 600'</u>					
<u>3 centralizers @ 1206' - 1146' - 1106'</u>					
<u>Lost returns @ 663'</u>					
<u>Lost dily back @ 980'</u>					

water sands

711' - 110' - 110'