

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>McDox Energy Corp</u>		Lease <u>State 32</u>		Well # <u>1</u>	
Location of Well	Unit <u>I</u>	Section <u>32</u>	Township <u>18</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor			Type of Equipment <u>April 15, 1978</u>		
* witness					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/4</u>	<u>13 3/8</u>	<u>48 #</u>		<u>350</u>	<u>Circ-375</u>
* <u>11'</u>	<u>8 5/8</u>	<u>24 #</u>		<u>2000</u>	<u>Circ-1000</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>10.5 + 11.6 #</u>		<u>8500</u>	<u>300</u>
Casing Data:					
Surface <u>49</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>K-55</u>					
(Approved) (Rejected)					
Inspected by <u>M.S.</u> date <u>4/4/78</u>					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required <u>1150</u>					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>2012'</u> Set <u>2012'</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>K-55</u>					
New-used csg. @ <u>2012'</u> with <u>200</u> sacks neat cement around shoe					
+ <u>200</u> sax <u>thix</u> additives <u>10 pd gillamite, 1/4 pd flocc, 270 cc</u>					
Plug down @ <u>11:20</u> (AM) (PM) Date <u>4/5/78</u>					
Cement circulated <u>yes</u> No. of Sacks <u>320</u>					
Cemented by <u>Halliburton</u> Witnessed by <u>Mike Stutts</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>+750 sacks Hall. Lite - 5 pd gillamite, 1/4 flocc.</u>					
<u>3 centralizers @ 1984'-1919'-1840'</u> <u>1 Basket @ 900'</u>					
<u>1796' Last break.</u>					

Possible Water Sands 485'-502'
548'-545'
722'-818'