

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 11 1978

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State <input type="checkbox"/> Fed <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name
Rio Pecos "GB" Com
9. Well No.
1 2
10. Field and Pool, or Wildcat Und.
Red Lake Penn. Morrow
12. County
Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator
Yates Petroleum Corporation
3. Address of Operator
207 South 4th Street - Artesia, NM 88210
4. Location of Well
UNIT LETTER L 1980 FEET FROM THE South LINE AND 1100 FEET FROM
THE West LINE, SECTION 20 TOWNSHIP 18S RANGE 27E NMPM.
15. Elevation (Show whether DF, RT, CR, etc.)
3290' CR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 9:00 AM 6-24-78.

TD225' - Ran 6 joints of 13-3/8" 48# H-40 (229') of casing set at 225'.
Cemented w/200 sacks of Class C 4% CaCl. Slurry wt. 14.8#, 1.32 cu. ft./sx.
Compressive Strength at 70 deg 1023 psi in 12 hours. PD 6:00 AM 6-26-78.
WOC and cement fell back and filled hole w/3yards of Ready-mix. WOC 12 hours
and cut off, reduced hole to 12¼", drilled plug and tested to 600#. OK.
Resumed drilling.

TD 1558' - Ran 39 joints of 8-5/8" casing J-55 24# (1579') set at 1558'. 1-
Guide shoe at 1558', insert float at 1518' and 3 centralizers and 2 cement
baskets. Cemented as follows: 500 sacks Howco Lite 10#/sack gilsonite, 1/4#
flocele, 2% CaCl. Tailed in w/150 sacks of Class C 2% CaCl. PD 5:30 PM
6-29-78. Cement circulated 10 sacks to surface. WOC 18 hours NU and tested
BOP's to 1500#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#.
OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson

TITLE Geol. Secty.

DATE 7-10-78

APPROVED BY Mark Williams

TITLE OIL AND GAS INSPECTOR

DATE JUL 11 1978

CONDITIONS OF APPROVAL, IF ANY: