

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Jules Petr. Corp.</i>		Lease <i>Rio Pecos Grb Com.</i>		Well # <i>2</i>	
Location of Well	Unit <i>19800</i>	Section <i>20</i>	Township <i>18</i>	Range <i>27</i>	County <i>Chisly</i>
Drilling Contractor <i>Marance</i>			Type of Equipment <i>Rotary</i>		
* <i>Witness</i>					
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8</i>	<i>48</i>		<i>250'</i>	<i>175 circ.</i>
* <i>12 1/4</i>	<i>8 5/8</i>	<i>24</i>		<i>1500'</i>	<i>850</i>
<i>7 7/8</i>	<i>4 1/2 or 5 1/2</i>	<i>105-117</i>		<i>9900</i>	<i>250</i>
Casing Data:					
Inter. _____					
Surface _____ joints of <i>8 5/8</i> inch <i>24</i> # Grade <i>J-55</i>					
(Approved) (Rejected)					
Inspected by <i>M. S.</i> date <i>6/27/78</i>					
Cementing Program					
Size of hole <i>12 1/4</i> Size of Casing <i>8 5/8</i> Sacks cement required <i>650</i>					
Type of Shoe used <i>guide</i> Float collar used <i>yes</i> Btm joints welded <i>yes</i>					
TD of hole <i>1558'</i> Set <i>1557'</i> Feet of <i>8 5/8</i> Inch <i>24</i> # Grade <i>J-55</i>					
New-used csg. @ <i>1558'</i> with <i>150</i> <i>22</i> sacks neat cement around shoe					
+ <i>500</i> sack <i>Hall Site</i> additives <i>1/4 lb. 10# gelignite, 270 cc</i>					
Plug down @ <i>5:30</i> (AM) (PM) Date <i>6/29/78</i>					
Cement circulated <i>yes</i> No. of Sacks <i>25</i>					
Cemented by <i>Halliburton</i> Witnessed by <i>Mike Stuppfield</i>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks:					
<i>2 Baskets @ 960' + 660'</i>					
<i>Last dily. Break @ 1095'</i>					