

5 - USGS - Artesia
1 - File
1 - Hal Owens - Engr.

N. M. O. C. C. COPY

Copy to SF

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029420-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ RECEIVED

2. NAME OF OPERATOR

Getty Oil Company

JUN 26 1978

3. ADDRESS OF OPERATOR

P. O. Box 730, Hobbs, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

810' FNL & 1980' FWL

7. UNIT AGREEMENT NAME

Skelly Unit

8. FARM OR LEASE NAME

Skelly Unit

9. WELL NO.

137

10. FIELD AND POOL, OR WILDCAT

Fren 7 - Rivers

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T-17-S, R-31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3787' GR

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 7-7/8" hole to 2550'. PBTD - 2508' 5-11-78.
2. Ran 64 Jts. (2540') 5-1/2" OD 15.5 K-55 8rd R3 Cond. A and set @ 2550'.
3. Dowell cemented W/625 sxs. 50/50 Poz; 4% Gel and 1/4# Flo-cele; 10# Salt plus 200 sxs. Class "C" Cement W/2% CaCl. Displaced cement to 2508'. Cement circulated.
4. Tested casing to 1000# for 15 minutes with no drop in pressure.

RECEIVED
JUN 23 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

Original Signed By

SIGNED Dale R. Crockett

TITLE Area Superintendent

DATE 6/20/78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE JUN 26 1978