

COPY UNITED STATES  
NMOCC DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 0630	
2. NAME OF OPERATOR Amoco Production Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Drawer A, Levelland, Texas 79336		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 1980' FEL Sec. 9 (Unit 0, SW/4 SE/4)		8. FARM OR LEASE NAME Yates Federal "B" Gas Com	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3528.7 GR		10. FIELD AND POOL, OR WILDCAT Richard Knob-Morrow	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 9-18-25	
		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud, intermediate casing ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 5-4-78 Delta Drilling Co. (Rig #60) spudded a 17 1/2" hole at 7:30 PM. Drilled to TD of 405' and set 13 3/8" 48# H-40 ST&C casing at 405'. Cement with 400 sacks Class C. Plug down 2:15 PM 5-12-78. Circulated 35 sacks. WOC 18 hrs. Test casing with 500# for 30 min. OK. Reduced hole to 12 1/4" and resumed drilling.

Drilled to TD of 1495' and set 8 5/8" 32# K-55 ST&C casing at 1495'. Cemented with 300 sacks thick set and 850 Howco lite and 200 sacks Class C. Plug down 4:30 PM 5-16-78. Circulated 45 sacks. WOC 30 hrs. Test casing with 1500# for 30 min. OK. Reduced hole to 7 7/8" and resumed drilling.

RECEIVED  
MAY 30 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

## 18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Admin. Analyst

DATE

5-26-78

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

APPROVED BY

TITLE

DATE

JUN 05 1978

CONDITIONS OF APPROVAL, IF ANY:

04-USGS-A  
1-Div  
1-Susp  
1-AVH  
1-Yates

\*See Instructions on Reverse Side