1-Houston

UN:D STATES DEPARTMENT OF THE INTERIOR	budget buleau No. 42-111424
	5. LEAGE NM-0630
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
aservoir, Use Form 9-331-C for such proposats.) 1. oil	8. FARM OR LEASE NAME Yates Federal B Gas Com
well well other Abandon/	9. WELL NO.
2. NAME OF OPERATOR Amoco Production Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Drawer "A", Levelland, Texas 79336 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Richard Knob Morrow 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 9-18-25
below.) AT SURFACE: 660' FSL & 1980' FEL, Sec 9 AT TOP PROD. INTERVAL: (Unit 0, SW/4 SE/4)	12. COUNTY OR PARISH 13. STATE Eddy NM
AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3543 RDB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: SEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE FEPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
ABANDON* X Other)	all participant details, and give participant dates
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details, and give pertinent dates, irrectionally drilled, give subsurface locations and

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Evaluated well and determined it was not commercially productive. Propose to plug and abandon well using the following procedure. Spot 80 sx Class H cement plug 8250'-8460'. Spot 60 sx Class H cement plug 3250'-3400'. Spot 40 sx Class H cement plug 1450'-1500'. Spot 10 sx Class H cement plug at surface. Erect P xA marker. Level and clean up location.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify/that the foregoing is true and correct	
SIGNED Kay Cox TITLE Admin. Superv	ison date April 19, 1979
APPROVED BY CONDITIONS OF APPROVAL, IF ANY: 0+4-USGS, A 1-Yates, A 1-RWA	fice use) ENGINEER DATE JUN 1 9 1979
0+4-USGS,A 1-Yates,A 1-RWA 1-Susp	

*See Instructions on Reverse Side