

5-USGS-ARTESIA
1-HAL OWENS - ENGR
1-ED FOWLER-FOREMAN

1-FILE
1-A.B. CARY-MIDLAND

Copy to 87
N.M. D.C. C. CORR

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-029420-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. **RECEIVED**

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 730, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

UNIT LETTER "K", 2130' FSL & 1980' FWL

JUL 17 1978

O. C. C.

ARTESIA OFFICE

7. UNIT AGREEMENT NAME

SKELLY UNIT

8. FARM OR LEASE NAME

SKELLY UNIT

9. WELL NO.

155

10. FIELD AND POOL, OR WILDCAT

FREN 7-RIVERS

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 28, T-17-S, R-31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3772'

12. COUNTY OR PARISH 13. STATE

EDDY

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

5-29-78: Drilled 7-7/8" hole to 2680'. Ran 67 Jts. 5-1/2" OD R3 K-55 ST&C Casing and set at 2678'. B.J. cemented w/800 sxs. Class "C" Cement with 2% AZ, 10# Salt, 1/4# Flo-Cel/Sk; and 200 sxs. Class "C" Cement w/2% CaCl/sk. Cement circulated. Tested 5-1/2" casing to 1500#. O.K.

RECEIVED

JUL 12 1978

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett
Dale R. Crockett

TITLE

AREA SUPERINTENDENT

DATE

6-28-78

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

APPROVED BY

Albert K. Fial

TITLE

DATE

JUL 14 1978

CONDITIONS OF APPROVAL, IF ANY: