

NMOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR. CATE*
(Other instructions on re-
verse side)

Copy to SF
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM 0924
2. NAME OF OPERATOR Hondo Drilling Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Drawer 2516, Midland, Texas 79702	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' from South line and 1980' from East line, Unit 0	8. FARM OR LEASE NAME Alscott Federal
14. PERMIT NO.	9. WELL NO. 3
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 3398' GR	10. FIELD AND POOL, OR WILDCAT North Turkey Track Morrow
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31 - T18S - R29E
	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

RECEIVED

JUN - 5 1978

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

16. NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
ARTESIA OFFICE		WATER SHUT-OFF	REPAIRING WELL
TEST WATER SHUT-OFF		FRACTURE TREATMENT	ALTERING CASING
FRACTURE TREAT		SHOOTING OR ACIDIZING	ABANDONMENT*
SHOOT OR ACIDIZE		(Other)	
REPAIR WELL		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
(Other)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

May 24 & 25, 1978 Building location.

May 26, 1978 Moving rig and rigging up rotary tools.

May 27, 1978 Rigging up rotary tools, spudded 17-1/2" hole at 6:00 P. M.

May 28, 1978 Drilled 17-1/2" hole to 411', ran 9 joints 13-3/8" 48 lb. H-40 casing, total of 415', set at 410'. Cemented with 425 sacks Class "C" 2% calcium chloride, cement circulated. Plug down at 10:00 A. M.

May 29, 1978 Tested 13-3/8" casing 1,000 lb. pressure test for 30 minutes without pressure drop W.O.C. 13-3/8" casing.

May 30, 1978 Drilling 11" surface hole at 822' 8:00 A. M.

RECEIVED
JUN 11 1978
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Albert R. Stall TITLE President DATE May 31, 1978

(This space for Federal or State office use)

APPROVED BY Albert R. Stall TITLE ACTING DISTRICT ENGINEER DATE JUN 02 1978

CONDITIONS OF APPROVAL, IF ANY: