

Form 9-331
(May 1983)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 2 APPLICATIONS
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0924

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		RECEIVED	
2. NAME OF OPERATOR Hondo Drilling Company		JUN 14 1978	
3. ADDRESS OF OPERATOR Drawer 2516, Midland, Texas 79702		D. C. C. ARTESIA, OFFICE	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement. See also space 17 below.) At surface 660' from South line and 1980' from East line, Unit 0		10. FIELD AND POOL, OR WILDCAT North Turkey Track Morrow	
14. PERMIT NO.		15. ELEVATIONS (Show whether DP, RT, GR, etc.) 3398' GR	
12. COUNTY OR PARISH Eddy		13. STATE New Mexico	

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Alscott Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

North Turkey Track Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31 - T18S - R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

May 30, 1978 Drilling 11" surface hole from 411' to 3015', total depth 11" surface hole

June 3, 1978 Ran 74 joints of 8-5/8" casing, 23 joints of 32 lb. K-55 ST&C, 909.94' and 51 joints of 24 lb. K-55 ST&C. 2113.30 ft. total of 3023.24 ft. Set at 3015 ft. Cemented with 1,000 sacks HowCo. Light cement containing 5 lb./sack gilsonite, 1/4 lb./sack Flocele, 2% calcium chloride and 200 sacks of Class C with 2% calcium chloride, cement circulated; plug down at 11:00 P.M.

June 4, 1978 Set slips on 8-5/8" casing, W.O.C. 8-5/8" casing 24 hours, pressure tested blowout preventers and 8-5/8" casing with 3,000 lb. pressure, without pressure drop.

June 5, 1978 Drilling 7-7/8" hole at 3215 ft. 8:00 A.M.

RECEIVED

JUN 9 1978

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Albert K. Hall

TITLE President

DATE June 8, 1978

(This space for Federal or State office use)

APPROVED BY

Albert K. Hall

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 13 1978

CONDITIONS OF APPROVAL, IF ANY: