

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gates Petr. Corp.</i>		Lease <i>Rio Pecos JX Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>6605 W 1980</i>	Section <i>35</i>	Township <i>18</i>	Range <i>25</i>	County <i>Elk</i>
Drilling Contractor <i>Imparance</i>			Type of Equipment <i>Rotary to start 8-14-78</i>		

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>350</i>	<i>250 circ.</i>
* <i>12 1/4"</i>	<i>8 5/8"</i>	<i>24</i>		<i>1150</i>	<i>550 "</i>
<i>7 7/8"</i>	<i>5 1/2 or 4 1/2"</i>			<i>9200</i>	<i>300</i>

Casing Data:

Int
~~S~~ *29* joints of *8 5/8* inch *24* # Grade *J-55*
✓ (Approved) (Rejected)

Inspected by *M.S.* date *8/18/78*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required *800*

Type of Shoe used *Guide* Float collar used *Insert* Btm 3 jts welded *Yes*

ID of hole *1150* Set *1217* Feet of *8 5/8* Inch *24* # Grade *J-55*

New-used csg. @ *1150* with *150* sacks neat cement around shoe - *2% CC*
+ *150* sack *Thick Set w/ 2% CC* additives + *500 SX Hanco Ltr - 10" 61/2 in. # F6 61/2 - 2% CC*

Plug down @ *2:00* (AM) (PM) Date *8/19/78*

Cement circulated *NO* No. of Sacks *—*

Cemented by *Halliburton* Witnessed by *MW*

Temp. Survey ran @ *8:00* (AM) (PM) Date *8/19/78* top cement @ *300'*

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Btm Wtr Sand @ 979' - Lost Circ @ 530'*

Centralizer @ 1133'

Centralizer + basket @ 500' + 1074'

13 3/8 @ 355' (48" - H-40) w/ 300 SX Class C - Circ 40 SX