

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
AMOCO PRODUCTION COMPANY ✓
3. ADDRESS OF OPERATOR
P.O. Drawer "A" Levelland, TX 79336
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' ~~FX~~ & 2200' FEL, Sec. 12
AT TOP PROD. INTERVAL: (Unit G, SW 1/4, NE 1/4)
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

OCT 18 1978

O. C. C.
ARTESIA, OFFICE

5. LEASE
NM 23413
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Empire South Deep Unit
8. FARM OR LEASE NAME
Empire South Deep Unit
9. WELL NO.
20
10. FIELD OR WILDCAT NAME
Und. South Empire-Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
12-18-28
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3641.7 RDB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Tested and evaluated well. Propose to plug and abandon using the following procedure. Use mud laden fluid between all plugs. Spot 80sx Class H cement plug (200') 10,518'-10,718' at middle of Morrow. Spot 95sx Class H cement plug (150') 9,665'-9815' at Strawn. Spot 60sx Class H cement plug (150') 8,405'-8,555' at Cisco. Spot 60sx Class H cement plug (150') 6,228'-6,378' at ABO. Spot 40sx Class H cement plug (100') 4,400'-4,500' at intermediate depth. Spot 50sx Class H cement plug (100') 2,800'-2,900' in and out of casing shoe at 2,850'. Spot 10sx surface plug (20'). Erect plug and abandonment marker. Clean and level location.

Procedure received verbal approval Mr. Ray Stoll, USGS in Artesia 9-21-78.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James Evans TITLE Asst. Admin. Analyst DATE 9-22-78

APPROVED BY Joe L. Lara (This space for Federal or State office use)
CONDITIONS OF APPROVAL, IF ANY: ACTING DISTRICT ENGINEER DATE OCT 17 1978

- 0+4 - USGS-A
1 - DIV
1 - SVSP
1 - DE

20-partners
1-Bright, Schiff, & Kennedy
2355 Stemmons Bldg. Dallas, TX 75207
*See Instructions on Reverse Side