

Form 9-331  
Sec. 1979  
**RECEIVED**

U. S. G. O. C. COPY

C:SR

UNITED STATES

**AUG 1 1979** DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

**O. C. C.**  
**ARTESIAN NOTICE**

**NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Abandon

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P.O. Drawer "A" Levelland, Texas 79336

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1980' FNL & 2200' FEL, Sec. 12  
AT SURFACE: (Unit G, SW 1/4, NE 1/4)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other)

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
NM 23413

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
Empire South Deep Unit Gas Com B

8. FARM OR LEASE NAME  
Empire South Deep Unit Gas Com B

9. WELL NO.  
20

10. FIELD OR WILDCAT NAME  
South Empire-Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
12-18-28

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3641.7 RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plug and abandoned well using the following procedure: spotted 80 sx cement plug 10,518'-10718'; spotted 95 sx cement plug 9665'-9815'; 60 sx cement plug 9405'-9555'; 60 sx cement plug 6228'-6308'; 40 sx cement plug 4400'-4500'; 50 sx cement plug 2800'-2900'; 10 sx cement plug to surface. Erected PxA marker. Rig released 9-23-78.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dennis Evans TITLE Asst. Admin. Analyst DATE 9-25-78

(This space for Federal or State office use)  
APPROVED BY (Orig. Sgd.) ALBERT A. STALL ACTING DISTRICT ENGINEER DATE JUL 31 1979

CONDITIONS OF APPROVAL, IF ANY:

0+4 - USGS A 20-Partners  
1 - DIV 1-Bright, Schiff, & Kennedy  
1 - SUSP 2355 Stemmons Bldg.  
1 - DE Dallas, Texas 75200

\*See Instructions on Reverse Side