

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	RECTANGULAR COORDINATES FEET	CLOSURE DISTANCE FEET	SURE DIRECTION D M	DOG LEG SEVERITY DEG/100FT
8896.	2 15	S 14 E	8893.89	22.40 S 45.32 E	50.55	S 63 42 E	3.3
8990.	3 45	S 1 E	8987.76	27.26 S 45.96 E	53.44	S 59 19 E	1.7
9084.	3 15	S 1 E	9081.58	33.00 S 46.06 E	56.66	S 54 23 E	.5
9178.	3 15	S 8 E	9175.43	38.31 S 46.48 E	60.23	S 50 30 E	.4
9272.	3 0	S 5 E	9269.29	43.40 S 47.06 E	64.01	S 47 19 E	.3
9366.	3 15	S 10 E	9363.15	48.48 S 47.72 E	68.03	S 44 33 E	.4
9460.	3 30	S 7 E	9456.99	53.95 S 48.54 E	72.58	S 41 59 E	.3
9554.	3 30	S 10 E	9550.81	59.63 S 49.39 E	77.43	S 39 38 E	.2
9648.	3 30	S 10 E	9644.64	65.28 S 50.39 E	82.46	S 37 40 E	0.0
9742.	3 15	S 16 E	9738.48	70.67 S 51.63 E	87.52	S 36 9 E	.5
9836.	3 15	S 15 E	9832.32	75.80 S 53.05 E	92.53	S 34 59 E	.1
9930.	3 0	S 17 E	9926.18	80.73 S 54.47 E	97.39	S 34 0 E	.3
10024.	3 0	S 16 E	10020.06	85.45 S 55.86 E	102.09	S 33 11 E	.1
10118.	2 45	S 9 E	10113.94	90.05 S 56.88 E	106.51	S 32 17 E	.5
10212.	2 30	S 10 E	10207.84	94.29 S 57.59 E	110.49	S 31 25 E	.3
10306.	2 30	S 5 E	10301.75	98.36 S 58.13 E	114.25	S 30 35 E	.2
10400.	2 30	S 3 E	10395.66	102.45 S 58.42 E	117.93	S 29 42 E	.1
10494.	2 30	S 4 W	10489.57	106.54 S 58.38 E	121.49	S 28 43 E	.3
10588.	2 15	S 2 W	10583.49	110.43 S 58.18 E	124.82	S 27 47 E	.3
10682.	2 15	S 1 W	10677.42	114.12 S 58.08 E	128.05	S 26 58 E	.0
10776.	2 0	S 4 E	10771.35	117.61 S 58.17 E	131.21	S 26 19 E	.3
10870.	2 0	S 6 E	10865.30	120.87 S 58.46 E	134.27	S 25 49 E	.1
10964.	2 30	S 23 E	10959.22	124.43 S 59.38 E	137.87	S 25 31 E	.9
1058.	2 0	S 10 E	11053.15	127.96 S 60.42 E	141.51	S 25 17 E	.8
11075.	2 0	S 10 E	11070.14	128.55 S 60.53 E	142.08	S 25 13 E	0.0

FINAL CLOSURE - DIRECTION: S 25 DEGS 12 MINS 47 SECS E
DISTANCE: 142.08 FEET