

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	RECTANGULAR COORDINATES FEET	CLOSURE DISTANCE FEET	DIRECTION D M	DOG LEG SEVERITY DEG/100FT
6076.	1 0	S 79 W	6075.52	.68 N 26.64 E	26.65	N 88 32 E	.5
6170.	0 30	N 64 W	6169.51	.84 N 25.44 E	25.45	N 88 7 E	.7
6264.	0 45	N 50 E	6263.50	1.69 N 25.33 E	25.39	N 86 10 E	1.1
6358.	0 30	N 21 W	6357.50	2.62 N 25.58 E	25.71	N 84 8 E	.8
6452.	0 45	N 69 W	6451.49	3.33 N 24.87 E	25.09	N 82 23 E	.6
6546.	1 0	S 82 W	6545.48	3.49 N 23.46 E	23.72	N 81 32 E	.5
6640.	1 0	S 55 W	6639.47	2.89 N 21.95 E	22.14	N 82 29 E	.5
6734.	1 15	S 47 W	6733.45	1.73 N 20.52 E	20.59	N 85 10 E	.3
6828.	1 45	S 56 W	6827.42	.20 N 18.59 E	18.59	N 89 22 E	.6
6922.	2 0	S 49 W	6921.36	1.67 S 16.15 E	16.24	S 84 6 E	.4
7016.	1 45	S 42 W	7015.31	3.82 S 13.96 E	14.47	S 74 41 E	.4
7110.	2 0	S 56 W	7109.26	5.84 S 11.65 E	13.03	S 63 23 E	.6
7204.	2 0	S 61 W	7203.21	7.55 S 8.85 E	11.63	S 49 32 E	.2
7298.	1 45	S 50 W	7297.16	9.29 S 6.32 E	11.23	S 34 14 E	.5
7392.	1 30	S 35 W	7391.12	11.25 S 4.52 E	12.12	S 21 54 E	.5
7486.	1 15	S 26 W	7485.09	13.19 S 3.38 E	13.62	S 14 22 E	.4
7580.	0 45	S 21 W	7579.08	14.69 S 2.72 E	14.94	S 10 30 E	.5
7674.	1 45	S 20 E	7673.05	16.70 S 2.71 E	16.92	S 9 12 E	1.4
7768.	4 15	S 48 E	7766.92	20.74 S 5.43 E	21.44	S 14 40 E	3.0
7862.	3 45	S 51 E	7860.69	25.00 S 10.42 E	27.08	S 22 37 E	.6
7956.	3 0	S 71 E	7954.52	27.67 S 15.23 E	31.58	S 28 50 E	1.5
8050.	2 45	S 85 E	8048.41	28.64 S 19.83 E	34.84	S 34 42 E	.8
8144.	3 0	S 88 E	8142.29	28.93 S 24.54 E	37.94	S 40 18 E	.3
8238.	2 30	N 89 E	8236.18	28.97 S 29.05 E	41.02	S 45 5 E	.6
8332.	2 0	N 75 E	8330.11	28.46 S 32.69 E	43.34	S 48 58 E	.8
8426.	1 45	N 69 E	8424.06	27.51 S 35.62 E	45.00	S 52 19 E	.3
8520.	1 30	N 51 E	8518.02	26.18 S 37.91 E	46.08	S 55 22 E	.6
8614.	1 30	N 56 E	8611.99	24.72 S 39.89 E	46.93	S 58 13 E	.1
8704.	1 15	N 45 E	8701.96	23.35 S 41.56 E	47.66	S 60 40 E	.4
8802.	1 15	N 43 E	8799.94	21.81 S 43.04 E	48.25	S 63 8 E	.0