

Anadarko

N.M. State A# 1

Elev - 3481.5 GL

RECEIVED BY

JUN 20 1984

O. C. D.  
ARTESIA, OFFICE

13 3/8" 48# casing to  
429'. Cemented with  
500 sk. Circ 170 sk.

429'

8 5/8" 38# + 24# casing  
to 3254'. Cemented with  
1000 sk. CT @ 775'

3254'

Casing stub after cut off  
above new CT

Hole in casing between 6922-7815

CT @ 775'

Loco Hills perms From 2180'-86'

110' cement plug From 3310' to 3200'

100' cement plug - 50' in casing + 50' out of casing.

New cement top @ 4000' ±.

CIBP @ 4500' with 35' cement on top.

CIBP @ 6385' with 35' cement on top

Blue Springs perms From 6416'-22'

Cement retainer above hole in casing. So CT  
Hole in casing can be brought up to 4000' ±.

CT @ 7500'

CIBP @ 8630' with 35' cement on top.

Wolfcamp perms From 8702-06

CIBP @ 9230' with 35' cement on top

Penn perms From 9244'-9402'

CIBP @ 9490'

Penn perms From 9538-42

CIBP @ 9920' with 35' cement on top.

Strom perms From 9951-73

CIBP @ 10500' with 35' cement on top.

Atoka perms From 10527-39

CIBP @ 10760' with 35' cement on top.

Morrow perms From 10794-959

4 1/2" N.6" casing to  
11074'. Cemented with  
775 sk. CT @ 9600'

11074'

PSTO @ Casing shoe = 11074'