

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION RECEIVED JUN
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
SEP 19 1984
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-7

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L - 1607

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Anadarko Production Company	8. Farm or Lease Name New Mexico State "AA"
3. Address of Operator P. O. Drawer 130, Artesia, New Mexico 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>35</u> TOWNSHIP <u>18S</u> RANGE <u>28E</u> N.M.P.M.	10. Field and Pool, or Wildcat Wildcat Upper Penn.
15. Elevation (Show whether DF, RT, GR, etc.) 3481.5' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER Recomplete (Bone Springs) ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- TOH with packer testing casing; found holes in casing from 5930' to 4505'.
- Ran wireline dump bailer and spotted 35' cement on top of CIBP @ 9210'.
- Set CIBP above Woldcamp perfs @ 8630'.
- Ran wireline dump bailer and spotted 35' cement on CIBP @ 8630'.
- Perforated 4 squeeze holes above cement top @ 7750'.
- Set cement retainer @ 7701'; cement out squeeze holes with 580 sx Class H cement with .8 of 1% CF-9, .2 of 1% AF-5 and 2% KCL.
- Ran Temp survey after 14 hours WOC and found C T @ 5650'
- Tripped in hole with packer.
- Perforated Bone Springs through tubing from 6416' to 6422' - 13 holes with .24" diam.
- Acidized with 800 gals 15% NE-FE acid.
- Swabbed back load and showed a trace of oil and gas.
- Zone not productive; will move up and recomplete in Grayburg Zone.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Brumwell TITLE Field ForemanDATE Sept. 19, 1984

APPROVED BY Original Signed By
Leslie A. Clements
CONDITIONS OF APPROVAL, IF ANY: Supervisor District II

TITLE

DATE SEP 25 1984