STATE OF NEW MEXICO	
ENERGY AND MINERALS DEPARTMENT OIL CONSERVATION DIVRECEIVED BY	
DISTRIBUTION P. O. BOX 2088	Form C-103 Revised 10-1-78
SANTA FE, NEW MEX CO SEP 11 1985	5. Indicate Type of Lease
LAND OFFICE O. C. D.	State XX Fee
OPERATOR ARTESIA, OFFICE	5 State Oil & Gas Lease No. L - 1607
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for for domasts to drill on to deepen of plug back to a different reservoir. Use "Application for Permit -" (FORM C-101) for such proposals.)	
1	7. Unit Agreement Name
OIL CX GAS WELL OTHER-	
Anadarko Production Company	8. Farm or Lease Name New Mexico State "AA"
3. Address of Operator P. O. Drawer 130, Artesia, New Mexico 88210	9. Well No.
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER 1980 FEET FROM THE NOTTH LINE AND 1980 FEET FROM	Loco Hills
THE West LINE, SECTION 35 18S 28E	$(\mathbf{A}) = \mathbf{A} $
15. Elevation (Show whether DF, RT, GR, etc.)	
3481.5' GL	12. County Eddy
16. Check Appropriate Box To Indicate Nature of Notice, Report or O	ther Data
NOTICE OF INTENTION TO: SUBSEQUEN	IT REPORT OF:
PERFORM REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
OTHER Recomplete (Los	co Hills) 🕅 🕅
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, includin work) SEE RULE 1703.	g estimated date of starting any proposed
<ol> <li>TOH with packer.</li> <li>Set CIBP, above Bone Springs perfs, @ 6385'.</li> </ol>	
3. Ran wireline dump bailer and spotted 35' cement on CIBP @ 6385'	
4. Ran single curve bond log to locate free pipe. 5. Shot off 4½" casing at 5490'; tripped out of hole with casing.	
6. WIH with tubing and circulated hole with 10# brine and salt gel mud.	
7. Spotted 65 sx Class H cement with 5% CaCl from 5650' to 5350' to cover $4\frac{1}{2}$ ' casing stub. 8. Waited 3 hours and tagged top of plug at 5384'.	
9. Spotted 75 sx Class H cement with 5% CaCl from 4850' to 4650' to cover Abo formation top. 10. Waited 3 hours and tagged top of plug at 4657'.	
11. Spotted 80 sx Class H cement with 57. CaCl from 3350' to 3100' to cover 8-5/8' casing shoe.	
<ol> <li>Waited 3 hours and tagged top of plug at 3100'.</li> <li>Perforated Loco Hills pay of Grayburg Zone from 2180' to 2186' - 1</li> </ol>	3 holes with .50" diam.
14. Acidized perforations with 500 gals 15% NE-FE acid and 20 BS.	
<ol> <li>15. Fraced Loco Hills with 26,000 gals gel, 16,000# 20/40 sand &amp; 20,00</li> <li>16. Ran tubing and rods.</li> </ol>	
17. Placed well on production.	Pure Der
	Pind
	Y
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Area Supervisor	October 26, 1984
- // // maren	
A 200 VED BY TITLE	- 1 DATE
CONDITIONS OF APPROVAL, IF ANY:	