

DISTRIBUTION		
SANTA FE	/	
FILE	/	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	/	

W MEXICO OIL CONSERVATION COMMISSION

Form C-100
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

NOV 29 1978

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-5004
7. Unit Agreement Name
8. Farm or Lease Name Cities "JG" St. Com
9. Well No. 1
10. Field and Pool, or Wildcat Undes. Morrow
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH OR FOR USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-
ARTESIA, OFFICE

2. Name of Operator
Yates Petroleum Corporation ✓

3. Address of Operator
207 South Fourth Street - Artesia, NM 88210

4. Location of Well
UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 13 TOWNSHIP 18S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3651' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Set 4½" Prod. Csg.</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1f03.

TD 8900'; WLPBTD 8869'. - Ran 235 joints of 4½" 10.5# and 11-6# K-55 (8924') of casing as follows: 71 joints 11.6# (2057'), 117 joints 10.5# (5217') and 47 joints of 11.6# (1650') set at 8900'. 1-Guide Shoe at 8900', Diff-Fill Collar at 8868' and 9 centralizers. Cemented as follows: 250 gallons of mud flush, 210 sacks of Class C 2/10% Halad-22, 3/10% CFR-2, 5#/sx KCL, 350 sacks Howco-lite, 2/10% Halad-22, 3/10% CFR, 25#/sx KCL tailed in w/260 sacks Class H 2/10% Halad-22, 3/10% CFR-2, 5#/sack KCL. PD 1:30 PM 11-23-78. WOC and ran Temperature Survey, found top of cement at 5820'. WLPBTD 8869'. Tested to 1500#. OK..

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 11-28-78

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE NOV 30 1978

CONDITIONS OF APPROVAL, IF ANY: