

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN 2 PLICATE\*  
(Other Instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

NM - 0924

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

FEB 14 1979

2. NAME OF OPERATOR

Hondo Drilling Company ✓

3. ADDRESS OF OPERATOR

Drawer 2516, Midland, Texas 79702

O. C. C.  
ARTEZIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FNL, 1980' FEL Section 30, T18S, R29E Unit G

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Fed. Alscott Com.

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

N. Turkey Track Morrow  
11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

30-T18S, R29E, NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3498 GR

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

January 26 to 31, 1979 Drilling 11" surface hole from 395' to 3015' total depth  
11" surface hole.January 31, 1979 Ran 72 joints 8 5/8" casing, 858.01 ft. 32 lb. K-55 ST&C & 2161.12  
ft. of 24 lb. K-55ST&C total of 3019.13 ft. Set at 3015 ft. cemented with 1400  
sacks HowCo Light cement and 200 sacks of Class "C" with 2% calcium chloride, cement  
circulated, plug down at 8:30 P. M.February 1, 1979 - Set slips on 8 5/8" casing, w.o.c. 8 5/8" casing 24 hours pressure  
tested blowout preventers and 8 5/8" casing with 3,000 lb. pressure, without pressure  
drop.

February 2, 1979 - Drilling 7 7/8" hole at 3450' at 8:00 A. M.

RECEIVED  
FEB 5 1979  
U.S. GEOLOGICAL SURVEY  
ARTEZIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE President

DATE February 2, 1979

TITLE ACTING DISTRICT ENGINEER

DATE

FEB 12 1979