Form 3160-5 (July 1989) (Formerly 9-331)	U DEPARTM	MM Roswell District Hodified Form No. N1060-3160-4  5. LEASE DESIGNATION AND SERIAL NO. NM 56426				
BUREAU OF LAND MANA REPORTS ON WELLS					6. IF INDIAN, ALLOTTER OR TRIPE NAME	
	s form for proposal	s to drill or to	deepen or plug back	toraidMedent reservoir.		
I.	Use "APPLICAT	ION FOR PERM	AIT LA	Bulli 20	7. UNIT AGBREMENT NAME	
OIL GAS WELL WELL	D OTHER		0100	1 2 Mg 15 1		
2. NAME OF OPERATOR			AREA	3a. Area Code & Thom	- 1	
	Drilling Com	pany /	Prive-	(915) <b>RECEIVE</b>	Sivley Federal	
3. ADDRESS OF OPERAT		· 11 . 1 m	v 20200 05	17	#2	
4. LOCATION OF WELL	awer 2516, M (Report location clea	idland, T	X 79702-25 ordance with any Sta	ite requirement MAR 28 1	_ 1	
See also space 17 be At surface	dow.)	South Loco Hills O.G.S.A.				
1,980' F	NL and 1,980	' FEL, Un	it Letter G	O. C. I	D. 11. SEC., T., R., M., OR BLE. AND SURVEY OR ARMA	
Sec. 30,	T-18-S, $R-2$	9-E		ARTESIA, OI	FFICE   Sec. 30, T-18-S, R-29-E	
14. PERMIT NO.		12. COUNTY OR PARINH 13. STATE				
30-015-2	2770 I		GR 3,498		Eddy New Mexico	
<u> </u>						
	* *		to indicate 14ar	ure of Notice, Report,		
	NOTICE OF INTENT	ON 10:	11	80	TRAEQUENT REPORT OF:	
TEST WATER SHUT	1 1	LL OR ALTER C	} -	WATER SHUT-OFF	REPAIRING WELL,	
FRACTURE TREAT		LTIPLE COMPLE Andon*	TE.	PRACTURE TREATMENT SHOOTING OR ACIDIZING	ALTERING CARING  ABANDONMENT®	
RIPAIR WELL		ANGE PLANS		(Other) Re-entr		
(Other)	L;			(Nork: Report re	esuits of multiple completion on Well completion Report and Log form.)	
17. DESCRIBE PROPOSED proposed work, nent to this work.	If well is direction	trions (Clearly ally drilled, giv	state all perfinent de subsurface location	letails, and give pertinent	dates, including estimated date of starting any vertical depths for all markers and gones perti-	
3-09-90	Rigged up d	rilling r	ig, picked u	p drill collars	and 4 1/2" drill pipe.	
3-10-90	Girculated hole, clean out 8 5/8" casing to 2,600' with 7 7/8" bit. Ran squeeze tool in hole, cemented perforations in 8 5/8" casing from 2,298' to 2,306' - 9 holes, 2,330' to 2,334' - 5 holes, 2,342' to 2,346' - 5 holes, with 150 sacks Halliburton Neat Cement and waiting on cement.					
3-11-90	3-11-90 Drill out cement Bridge Plug and circulate hole to 2,600'. Test 8 5/8" casing to 1,000 lbs., Drill cement and Halliburton Bridge Plug at 2,950' in 8 5/8" casing.					
3-12-90	0-12-90 Circulate hole and clean out to 7,980' total depth. Condition mud, pulled out of hole and ran Schlumberger Logs.					
3-13-90	-90 Layed down drill pipe and collars, Ran 5 1/2" 17 1b. casing, depth - 7,928.37' Cement with 450 sacks Halliburton Neat Cement and waiting on cement.					
3-14-90	Moved dril	ling rig o	off location	and waiting on p	oulling unit.	
		•			ACCEPTED FOR RECORD	
18. I hereby coftiff th	Me Yarenottie la	true and correc	<u></u>		MAR 12 7 1990	
Ash	Weller,		TITLE	President	DATE March 21, 1990	
SIGNED			11106			
(This space for Federal or State office use)				CARUSBAD, NEW MEXICO		
APPROVED BY _ CONDITIONS OF	APPROVAL, TF AN	TY :	TITLE		DATE	