

UNIT STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
SUBMIT IN TRIPPLICATE  
(Other instructions on  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L C 060664

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lucia Brookes

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Leo Queen Grayburg

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 14-T18S-R30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR  
Estate of T. B. Knox ✓

3. ADDRESS OF OPERATOR  
112 N. First St., Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FSL - 1980' FWL, Section 14-T18S-R30E  
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3510.2 GR

RECEIVED

APR 11 1979

O. C. C.  
ARTESIA, OFFICE

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Surface casing program

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded well 3:00 p.m. 3-31-79. Drilled 12 3/4" hole to 551'. Ran 12 jts. of new 8 5/8" 8 round casing to 551'. Cemented with 250 sx 50/50 pozmix with 2% CaCl plus 1/4# flocele per sx, plus 100 sx Class C cement with 2% CaCl. Plug down 11:30 p.m. 3-31-79. Circulated out 75 sx to surface. After WOC 24 hrs., tested casing to 1,000# for 30 minutes. It held okay. Drilled out plug, tested casing at 800# for 30 minutes. Held okay. Drilling ahead with brine water.

RECEIVED

APR 3 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Paul G. White

TITLE Engineer

DATE 4-2-79

(This space for Federal or State office use)

APPROVED BY

C. J. STALL

TITLE

REGIONAL ENGINEER

DATE

APR 10 1979

CONDITIONS OF APPROVAL, IF ANY: