

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPI  
(Other instructions  
verse side)

TE\*  
re-

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-030752

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

RECEIVED

2. NAME OF OPERATOR

Hondo Drilling Company ✓

3. ADDRESS OF OPERATOR

P. O. Drawer 2516, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.  
At surface

1980' FWL, 660' FSL Section 28 T-18S R-29E Unit *MN*

MAR 23 1979

O. C. C.

ARTESIA, OFFICE

8. FARM OR LEASE NAME

Trigg-Jennings Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

N. Turkey Track - Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

28-T18S-R29E-NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3424 Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

March 7 to 11, 1979 Drilling 11" surface hole from 395' to 3015' total depth  
11" surface hole at 7:00 A. M.

Ran 69 joints 8 5/8" casing, 905.42 ft. 32 lb. K-55 ST&C and 2111.75 of 24 lb.  
K-55 ST&C, total of 3017.17. Set at 3015' cemented with 1300 sacks HowCo Light  
cement and 200 sacks of Class "C" with 2% calcium chloride, cement circulated,  
plug down at 1:30 A. M. 3/11/79.

March 12, 1979 W.O.C. 8 5/8" casing, set slips on 8 5/8" casing, pressure tested  
blow-out preventers and 8 5/8" casing with 3000 lb. pressure, for 30 minutes with-  
out pressure drop.

March 13, 1979 Drilling 7 7/8" hole at 3663' at 8:00 A. M.

RECEIVED

MAR 16 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE

President

DATE March 15, 1979

(This space for Federal or State office use)

APPROVED BY

*[Signature]*

TITLE

ACTING DISTRICT ENGINEER

DATE

MAR 21 1979

CONDITIONS OF APPROVAL, IF ANY: