

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

UNITED STATES
OFFICE FOR
OF COPIES
(Other instructions on re-
verse side)

RM Rowell District
Modified Form No.
NM60-3160-4

c/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Hondo Drilling Company

3. ADDRESS OF OPERATOR
P.O. Drawer 2516, Midland, TX 79702-2516

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1,980' FWL and 660' FSL, Sec. 28,
T-18-S, R-29-E, Unit M

14. PERMIT NO.
30-015-22784

15. ELEVATIONS (Show whether DF, RT, CR, etc.)
3,438' RKB

34. AREA CODE & PHONE NO.
(915) 682-9401

5. LEASE DESIGNATION AND SERIAL NO.
NM 030752

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Trigg Jennings Com

9. WELL NO.
#1

10. FIELD AND POOL, OR WILDCAT
North Turkey Track, Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28, T-18-S, R-29-E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other)	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Waiting on Pulling Unit to workover Trigg Jennings Well #1.

Pull 2 3/8" tubing and Guiberson Packer out of hole. Set cast iron Bridge Plug at 11,130'. Dump 40' cement on top of Bridge Plug. Plug back depth 11,090'.

Perforate Morrow Zone from 10,994' to 11,012', Total 18', 2 shots per foot.

Pressure Test 2 3/8" tubing in hole, set Guiberson Packer at 10,935'. Swab, Test well and Acidize well with 2,000 gal. 7 1/2% acid.

Frac well with 25,000 gal. of 60% Alcofoam with 20,900 lb. of propping agent.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE President DATE Jan. 25, 1991

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE DATE 1/30/91

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side