Form 3160-5 (August 1999)

Notice of Intent

Subsequent Report

Final Abandonment Notice

DEPA

FORM APPROVED
OMB No. 1004-0135
Expires November 30, 200

Water Shut-Off

🖸 Other Frac existing

Morrow perfs

☐ Well Integrity

UNITED STATES	24563	OMB No. 1004-0135
RTMENT OF THE INTERIOR	123456789	Expires November 30, 20
ALLOE LAND MANAGEMENT		C. Laure Carlel No.

Production (Start/Resume)

Temporarily Abandon

Water Disposal

☐ Reclamation

Recomplete

SUNDRY NOTICES AND N	EPUNIS UN WALLS	NM-2/2/0	
Do not use this form for proposa abandoned well. Use Form 3160-3	(APD) for such proposal RECEIVED 4	Received the state of the state	
SUBMIT IN TRIPLICATE - Other II	nstructions on reverse side ESIA	7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well Oil Well Gas Well Other	181920212223588	8. Well Name and No.	
2. Name of Operator Yates Petroleum Corporation		Benson Deep Unit #1 9. API Well No.	
3a. Address	3b. Phone No. (include area code)	30-015-22793	
105 S. 4th St Artesia, NM 88	3210 505-748-1471	10. Field and Pool. or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Desc.	ription)	Nime im Ridge Morrow	
660' FSL & 2180' FEL of Section 3		11. County or Parish, State	
		Eddy Co., NM	
12. CHECK APPROPRIATE BOX(E	S) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		

- Return to production 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)
 - 8-11-2000 Moved in and rigged up pulling unit.

☐ Acidize

Alter Casing

Casing Repair

Change Plans

Convert to Injection

- 8-12-2000 Bled well down. Loaded tubing with 2% KCL water. Nippled down wellhead
- and nippled up BOP. Released packer. TOOH with packer and tubing. Shut well in.

Deepen

Fracture Treat

☐ Plug Back

■ New Construction

Plug and Abandon

- 8-13-14-2000 Waiting on 3-1/2" P-110 frac string.
- 8-15-2000 Changed out pulling units.
- 8-16-2000 Circulated hole with 7% Super Fluid. TOOH and stand 2-7/8" tubing back.
- in hole with packer, on/off tool with 2.25" F profile and 3-1/2" tubing. Shut down.
- 8-17-2000 Finished TIH with packer and tubing. Nippled down BOP. Set packer at 11305'.
- Nippled up wellhead. Tested annulus to 1600 psi, OK. Shut well in.
- 8-18-2000 Frac'd perforations 11538-11615' (Morrow) with 15000 gallons 700 foam, 34000#
- 20-40 interprop and 6250# 20-40 econoflex. Opened well and began flowing back frac.
- 8-19-2000 Flowed well back. Flow testing.
- 8-20-2000 Flow testing.
- 8-21-2000 Flow testing.
- 8-22-2000 Loaded tubing with 7% super fluid (50 bbls). Nippled down wellhead and nippled

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Operations Technician Rusty Klei Signature August 31, 2000 THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Date Approved by Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease Office which would entitle the applicant to conduct operations thereon.

YATES PETROLEUM CORPORATION Benson Deep Unit #1 Section 33-T18S-R30E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

up BOP. Released packer. Started TOOH with 3-1/2" tubing. Shut well in. 8-23-2000 - Bled well down. Killed well with 7% super fluid. TOOH with 3-1/2" tubing and laying down. Shut well in.

8-24-2000 - Bled well down. Killed well with 7% super fluid. Finished TOOH with 3-1/2" tubing and packer. TIH with packer, on/off tool with 1.875" F nipple and 2-7/8" tubing. Set packer at 11447'. Nippled down BOP and nippled up wellhead. Tested annulus to 500 psi, OK. Shut well in.

8-25-2000 - Bled well down. Swabbed & flow tested. Shut well in.

8-26-27-2000 - Flow testing.

8-28-2000 - Flow tested. Shut well in.

8-29-2000 - Released well to production department.

Rusty Klein

Operations Technician

August 31, 2000