Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

N.M. Oil Cas. Division 811 S. 1st Street

01515 FORM APPROVED OMB No. 1004-0135

Expires November 30, 2000

	BUREAU OF LAND MANA	AGEMENT AFU	esia, ivivi 88	2 1 0-2834 5. Lease Serial	I No
SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				NM	M-27276 Hottee or Tribe Name
SUBMIT IN TR	RIPLICATE - Other Instr	uctions on reverse s	ide S	7. If Unit or Ca	A/Agreement, Name and/or No.
1. Type of Well		\%\(\sigma\)	10 C	<b>l</b>	
Oil Well 🚨 Gas Well 🔲 Other				8. Well Name	and No.
2. Name of Operator				Bensor	n Deep Unit #1
Yates Petroleum (	Corporation	10	the SIA SIA	9. API Well N	lo.
3a. Address		3b. I'hone No. (include at	rea code)	30	0-015-22793
105 S. 4th St	Artesia, NM 88210			J	ool, or Exploratory Area
4. Location of Well (Footage, Sec		n) Li	138L997	Nimeni	m Ridge Morrow
660' FSL & 2180' F	FEL of Section 33-T	$18S-R30E$ (Unit $\mathfrak F$	, SWSE)	11. County or P	'arish, State
				Ec	ddy Co., NM
12. CHECK AF	PPROPRIATE BOX(ES) T	O INDICATE NATURE	OF NOTICE, RI	EPORT, OR O	THER DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
	Acidize	Deepen [	Production (Start	/Resume)	Water Shut-Off
Notice of Intent	☐ Alter Casing	= :	Reclamation	ĺ	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	KX.	Other Frac existing
	Change Plans		Temporarily Aba		Morrow perfs
Final Abandonment Notice	Convert to Injection		☐ Water Disposal		Return to production
Attach the Bond under which the following completion of the invitesting has been completed. Findetermined that the site is ready	ectionally or recomplete horizonta the work will be performed or pro volved operations. If the operatio inal Abandonment Notices shall I	illy, give subsurface locations ovide the Bond No. on file wit in results in a multiple complet be filed only after all requiren	and measured and tru In BLM/BIA. Requir tion or recompletion i	e vertical depths o ed subsequent rep in a new interval, :	and approximate duration thereof. of all pertinent markers and zones, ports shall be filed within 30 days a Form 3160-4 shall be filed once n completed, and the operator has
8-12-2000 - Noveu	vell down. Loaded	tubing with 2% K(	CL water. N	ippled dow	n wellhead
and pippled up ROP	P. Released packer	. TOOH with pack	ker and tubi	ng. Shut	well in.
8-13-14-2000 - Wai	Iting on $3-1/2$ " P-1	10 frac string.		0	
	ed out pulling unit				
8-16-2000 - Circul	lated hole with 7%	Super Fluid. TO	OH and stand	2-7/8" tu	ibing back. Started
in hole with packe	er, on/off tool wit	h 2.25" F profile	e and 3-1/2"	tubing.	Shut down.
9 17 2000 Finish	and TIU with packer	and tubing Ni	onled down R	OP Set r	packer at 11305'.

8-17-2000 - Finished TIH with packer and tubing. Nipp Nippled up wellhead. Tested annulus to 1600 psi, OK. Shut well in.

8-18-2000 - Frac'd perforations 11538-11615' (Morrow) with 15000 gallons 70Q foam, 34000#

20-40 interprop and 6250# 20-40 econoflex. Opened well and began flowing back frac.

8-19-2000 - Flowed well back. Flow testing.

8-20-2000 - Flow testing.

8-21-2000 - Flow testing.

8-22-2000 - Loaded tubing with 7% super fluid (50 bbls). Nippled down wellhead and nippled

Name (Printed/Typed) Rusty K1e1n	Title	Operations Techn	ician
Signature Kustur Vulum	Date	August 31, 2000	
THIS SPACE FOR FEDER	RAL OR	STATE OFFICE USE	Contract of the second
Approved by		Title	Date NO!/
Conditions of approval, if any, are attached. Approval of this notice does not wa certify that the applicant holds legal or equitable title to those rights in the subjewhich would entitle the applicant to conduct operations thereon.	errant or ect lease	Office	77 2030
			and the state of t



YATES PETROLEUM CORPORATION Benson Deep Unit #1 Section 33-T18S-R30E Eddy County, New Mexico

## SUNDRY NOTICE CONTINUED:

up BOP. Released packer. Started TOOH with 3-1/2" tubing. Shut well in. 8-23-2000 - Bled well down. Killed well with 7% super fluid. TOOH with 3-1/2" tubing and laying down. Shut well in. 8-24-2000 - Bled well down. Killed well with 7% super fluid. Finished TOOH with 3-1/2" tubing and packer. TIH with packer, on/off tool with 1.875" F nipple and 2-7/8" tubing. Set packer at 11447'. Nippled down BOP and nippled up wellhead. Tested annulus to 500 psi, OK. Shut well in. 8-25-2000 - Bled well down. Swabbed & flow tested. Shut well in. 8-26-27-2000 - Flow testing.

8-28-2000 - Flow tested. Shut well in.

8-29-2000 - Released well to production department.

Rusty Klein

Operations Technician

August 31, 2000

NOV 1.7 2000