

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Hondo Drilling Co.</i>		Lease <i>Hondo-Kelly Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>6603 1980W</i>	Section <i>27</i>	Township <i>18</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor <i>Hondo Drilling Co.</i>			Type of Equipment <i>Rotary to start approx. 2-28-79</i>		

APPROVED CASING PROGRAM

* *witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8"</i>	<i>48</i>		<i>380</i>	<i>circ.</i>
<i>11"</i>	<i>8 5/8"</i>	<i>24</i>		<i>1250</i>	<i>circ.</i>
<i>7 7/8</i>	<i>4 1/2"</i>	<i>11.60</i>		<i>9500</i>	<i>550</i>

Casing Data:

Surface _____ joints of *8 5/8* inch *24+32* # Grade *J-55*

(Approved) (Rejected)

Inspected by *M. S.* date *3/15/79*

Cementing Prog

Size of hole *11 1/4* Size of Casing *8 5/8* Sacks cement required _____

Type of Shoe used *guide* Float collar used *yes* Btm 3 jts welded *yes*

TD of hole *1250'* Set *1250'* Feet of *8 5/8* Inch *24+32* # Grade *J-55*

New-used csg. @ *1250'* with *175270cc* sacks neat cement around shoe
+ *325* sax *Hall's Lite* additives *5# gilsonite - 1/4 # floccul - 270cc*

Plug down @ *8:30* (AM) (PM) Date *3/16/79*

Cement circulated *No* No. of Sacks _____

Cemented by *Hall's Drilling* Witnessed by *M. S. Sturges*

Temp. Survey ran @ *3:30* (AM) (PM) Date *3/17/79* top cement @ *330'*

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

centralizers @ 1245'-1190'-850'

last log break @ 1030'