

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-104  
Effective 1-1-69

RECEIVED

MAR 20 1979

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Name of Lease Name Hondo-Kelly Com.
9. Well No. 1
10. Field and Foot, or Whistal Undesignated, Atoka Penn
12. County Eddy

**SUNDY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

**O.C.C. ARTEBIA, OFFICE**

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator  
Hondo Drilling Company

3. Address of Operator  
Drawer 2516, Midland, Texas 79702

4. Location of Well  
UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 27 TOWNSHIP 18-S RANGE 26-E NMFM.

15. Elevation (Show whether BF, FT, GR, etc.)  
3360' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASINGS <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 3/12/79 Rigging up Rotary tools.
- 3/13/79 Spudded 17 1/2" hole at 1:00 P. M. Drilled 17 1/2" hole to 380'. Ran 11 joints 13 3/8" 48 lb. H-40 casing, set at 380', cemented with 350 sacks Class "C" 2% calcium chloride. cement circulated. Plug down 11:00 P. M. 3/13/79.
- 3/14/79 Tested 13 3/8" casing 500 lb. pressure test for 30 minutes without pressure drop and w.o.c. 13 3/8" casing.
- 3/15/79 Drilling 11" hole at 876', 8:00 A. M.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE President DATE 3/17/79

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: