

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

FEB 14 1979

C. D. C.
ARTESIA, NEW MEX.

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Upham "KN"
3. Address of Operator 207 South Fourth Street - Artesia, NM 88210	9. Well No. 1 1
4. Location of Well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>18S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Und. West Atoka-Morro
15. Elevation (Show whether DF, RT, GR, etc.) 3488' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded a 17½" hole at 4:00 PM 2-3-79.

TD 375'. Ran 10 joints of 13-3/8" 48# H-40 (375') of casing set at 375'.
1-insert float at 335'. Cemented w/350 sacks of Class "C" 4% CaCl. Slurry
weight 14.8, 1.32 cu.ft/sack. Compressive strength at 70 degrees 1023 psi
in 12 hours. Cement circulated 50 sacks to surface. PD 9:40 AM 2-4-79.
WOC 12 hours. Backed off, reduced hole to 12¼", drilled plug and tested to
600#, OK. Resumed drilling.

TD 1246'. Ran 31 joints of 8-5/8" 24# K-55 (1244') of casing set at 1246'.
1-diff-fill float collar and 1 guide shoe. Cemented w/710 sacks of 50/50
poz 2% CaCl, 1/4# celloflake, 5#/sack Kolite. Tailed in w/150 sacks of
Class "C" 2% CaCl. PD 5:00 PM 2-10-79. Cement circulated 50 sacks to
surface. WOC and cement fell. Filled hole w/6 yards of Ready-Mix. Nippled
up, tested BOP's to 1300#, OK. Reduced hole to 7-7/8". Drilled plug and
tested to 600#, OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geological Secretary

DATE 2-13-79

APPROVED BY W. A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE FEB 15 1979

CONDITIONS OF APPROVAL, IF ANY: