

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-55

MAY 23 1979

O. C. C.

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L 2918	

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator MONSANTO COMPANY ✓ 3. Address of Operator 1330 Midland NBT, Midland, Tx. 79701 4. Location of Well UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 35 TOWNSHIP 18S RANGE 27E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 12. County Eddy	7. Unit Agreement Name 8. Farm or Lease Name APEX STATE COM 9. Well No. 1 10. Field and Pool, or Wildcat Wildcat Morrow
---	---

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER Spud <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17 1/2" hole 3:00 AM 5/19/79.
Drilled 17 1/2" hole to total depth of 366'.
Ran 9 Jts. 377', 13 3/8" new 48# H-40 ST&C Csg set at 366'; cemented to surface w/ 375 Sx.
Class C Cement w/ 1/4# D-29 & 5# D-42/Sx. + 2% CaCl₂; Plug down 5:30 AM 5/20/79.
WOC 24 Hrs and tested w/ 1000 psi for 30 Mins., held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Regional Prod. Mgr.

DATE 5/22/79

APPROVED BY [Signature]

TITLE SUPERVISOR, DISTRICT II

DATE MAY 24 1979

CONDITIONS OF APPROVAL, IF ANY: