

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other Instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-067136

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Scout LH Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT
Penasco Draw Morrow
Undesignated11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 27-18S-25E

Unit L NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL ☐ GAS ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM 88210 ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FWL of Section 27-18S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3529' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Set Prod. Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9063' - Ran 227 joints of 4½" 11.6# & 10.5# N-80 and K-55 casing as follows: 10 joints 11.6# N-80 (330'); 55 joints 11.6# K-55 (2220'); 118 joints 10.5# K-55 (4748') and 44 joints 11.6# K-55 (1778') (Total 9076') of casing set at 9063'. 1-Guide shoe at 9063'; Diff-Collar at 9023' and 9-centralizers. Cemented w/250 gallons mud flush, 700 sacks 50/50 Poz, 2/10% Halad-22, 5/10% CFR-2, 5#/sack KCL & 150 sacks Class H 2/10% Halad-22, 5/10% CFR-2, 5#/sack KCL displaced w/40 bbls 2% KCL water. PD 10:00 AM 9-12-79. Pressure tested to 2300#. OK. WOC 6 hours and ran Temperature Survey and found top of cement at 6020; WLPBTD 9057'.

RECEIVED

SEP 24 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE

Geol. Secty.

DATE

9-22-79

(This space for Federal or State office use)

APPROVED BY

GEOL. SEC. GEORGE H. LAWRENCE

TITLE

DATE

SEP 25 1979

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side