

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
 NOV 7 1979  
**O. C. C.**  
**ARTESIA, OFFICE**

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG-1727

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER -	7. Unit Agreement Name
2. Name of Operator Hanagan Petroleum Corporation	8. Farm or Lease Name Shamrock
3. Address of Operator P.O. Box 1737 - Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>34</u> TOWNSHIP <u>18S</u> RANGE <u>28E</u> NMPM.	10. Field and Pool, or Wildcat <u>Undesignated</u> <i>North Turkey Track</i>
15. Elevation (Show whether DF, RT, GR, etc.) 3568 KB	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
 NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input checked="" type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/17, 18 & 19/79 - T.D. 10661; set 35 sx. Class "H" 2% CaCl plug inside 8 5/8" csg., plug down 2:30 PM (10/17/79), tagged top plug @ 2440'. Ran 23 jts. 7" 23# L-80 flush jt. csg., set @ 1023' & cmt. w/100 sx. Class "C" 1/2 of 1% CFR2 + 6# salt/sx., cmt. didn't circ. p.d. 7:30 AM (10/18/79) WOC 24 hrs., ran temp. survey w/top cmt. @ 100'. Press. up on BOP & 7" csg. w/2000# for 30 mins. w/no press. drop, drld. out cmt. & shoe, press. up on 8 5/8" w/1000# no press. drop, drld out cmt. plug & began making new hole w/6 1/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Hugh E. Hanagan</u>	TITLE <u>Vice President</u>	DATE <u>10/25/79</u>
APPROVED BY <u>W. A. Gussor</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>NOV 8 1979</u>

CONDITIONS OF APPROVAL, IF ANY: