

depth of well, it shall be measured by a surveying instrument. In the case of functionally drilled wells, true vertical depth shall be reported. For multiple completion, the formation from 30 through 34 shall be reported for each completion. This form is to be filled in quarterly except on state land, where six copies are required, rule 1135.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	7398	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	7651	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	8058	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison
T. Queen	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya		T. Mancos	T. McCracken
T. San Andres	T. Simpson		T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee		Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	T.
T. Blinberry	T. Gr. Wash		T. Morrison	T.
T. Tubb	T. Granite		T. Todilto	T.
T. Drinkard	T. Delaware Sand		T. Entrada	T.
T. Abo	T. Bone Springs	8384	T. Wingate	T.
T. Wolfcamp	T. Mrwr Clastics		T. Chinle	T.
T. Penn.	T. Chester	8553	T. Permian	T.
T. Cisco (Bygones)	T.		T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 6544 to 6660	No. 4, from
No. 2, from to	No. 5, from to
No. 3, from to	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	770	770	Surface and red bed				
770	1167	397	Red bed				
1167	1281	114	Lime and shale				
1281	3044	1763	Anhydrite				
3044	3519	475	Lime and sand				
3519	3946	427	Dolo. lime				
3946	4293	347	Lime and sand				
4293	4580	287	Lime				
4580	5649	1069	Lime and sand				
5649	8630	2981	Lime and shale				