

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARRESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Gulf Oil Corp.</i>		Lease <i>Eddy 35 State Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980 11-2</i>	Section <i>3-2</i>	Township <i>18</i>	Range <i>24</i>	County <i>Eddy</i>
Drilling Contractor	Type of Equipment <i>Rotary to start before 11-1-79</i>				

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>14 3/4"</i>	<i>11 3/4"</i>	<i>42</i>		<i>400</i>	<i>300 cix</i>
<i>11</i>	<i>8 7/8"</i>	<i>24</i>		<i>1200</i>	<i>800 "</i>
<i>7 7/8"</i>	<i>5 1/2</i>	<i>15.5+17</i>		<i>9000</i>	<i>700 SX</i>

Casing Data:

Int
Surface *29* joints of *8 5/8* inch *24* # Grade *K-55*
☒ (Approved) ☐ (Rejected)

Inspected by *mw* date *11/10/79*

Cementing Program

Size of hole *11* Size of Casing *8 5/8* Sacks cement required *700 SX*

Type of Shoe used *Type M* Float collar used *Insert* Btm 3 jts welded *Yes*

TD of hole *1200* Set *1377* Feet of *8 5/8* inch *24* # Grade *K-55*

New-used csg. @ *1200* with *200* sacks neat cement around shoe

+ *200* sack thick set w/ *10* # *6* sine + *1/4* # *Flt* collar per *SX* + *300 SX* / *6* c w/ *5* # *6* sine + *1/4* # *Flt* collar per *SX*

Plug down @ *12:15* (AM) (PM) Date *11/10/79*

Cement circulated *Yes* No. of Sacks *175*

Cemented by *Halliburton* Witnessed by *NW*

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Btm wtr Sand @ 906*

No. Resists - 1 Centralizer @ 1158' + 1 @ 1076'