

This form is to be filed with the appropriate district Office of the Commission not later than \_\_\_\_\_ days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

### INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

#### Southeastern New Mexico

T. Anhy \_\_\_\_\_ T. Canyon 7,410'  
T. Salt \_\_\_\_\_ T. Strawn 7,798'  
B. Salt \_\_\_\_\_ T. Atoka 8,150'  
T. Yates \_\_\_\_\_ T. Miss (Sh) 8,596'  
T. 7 Rivers \_\_\_\_\_ T. Devonian \_\_\_\_\_  
T. Queen \_\_\_\_\_ T. Silurian \_\_\_\_\_  
T. Grayburg \_\_\_\_\_ T. Montoya \_\_\_\_\_  
T. San Andres \_\_\_\_\_ T. Simpson \_\_\_\_\_  
T. Glorieta 1,942' T. McKee \_\_\_\_\_  
T. Paddock \_\_\_\_\_ T. Ellenburger \_\_\_\_\_  
T. Blinebry \_\_\_\_\_ T. Gr. Wash \_\_\_\_\_  
T. Tubb 3,314' T. Granite \_\_\_\_\_  
T. Drinkard \_\_\_\_\_ T. Delaware Sand \_\_\_\_\_  
T. Abu 3,950' T. Bone Springs \_\_\_\_\_  
T. Wolfcamp 5,218' T. Yeso 2,090'  
T. Penn. \_\_\_\_\_ T. Bursum 6,320'  
T. Cisco (Bough C) 6,894' T. Morrow 8,436'

#### Northwestern New Mexico

T. Ojo Alamo \_\_\_\_\_ T. Penn. "B" \_\_\_\_\_  
T. Kirtland-Fruitland \_\_\_\_\_ T. Penn. "C" \_\_\_\_\_  
T. Pictured Cliffs \_\_\_\_\_ T. Penn. "D" \_\_\_\_\_  
T. Cliff House \_\_\_\_\_ T. Leadville \_\_\_\_\_  
T. Menefee \_\_\_\_\_ T. Madison \_\_\_\_\_  
T. Point Lookout \_\_\_\_\_ T. Elbert \_\_\_\_\_  
T. Mancos \_\_\_\_\_ T. McCracken \_\_\_\_\_  
T. Gallup \_\_\_\_\_ T. Ignacio Qtzte \_\_\_\_\_  
Base Greenhorn \_\_\_\_\_ T. Granite \_\_\_\_\_  
T. Dakota \_\_\_\_\_ T. \_\_\_\_\_  
T. Morrison \_\_\_\_\_ T. \_\_\_\_\_  
T. Todilto \_\_\_\_\_ T. \_\_\_\_\_  
T. Entrada \_\_\_\_\_ T. \_\_\_\_\_  
T. Wingate \_\_\_\_\_ T. \_\_\_\_\_  
T. Chinle \_\_\_\_\_ T. \_\_\_\_\_  
T. Permian \_\_\_\_\_ T. \_\_\_\_\_  
T. Penn. "A" \_\_\_\_\_ T. \_\_\_\_\_

#### OIL OR GAS SANDS OR ZONES

No. 1, from 6,450' to 6,560' No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from 8,410' to 8,590' No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

#### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet.  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet.

#### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1600	1860		Dolomite (trace Lime)	7390	8000		Limestone/shale
1860	1980		Dolomite (intermittent SS)	8000	8320		Lime/Shale/Intermittent SS
1980	2300		Dolomite (trace Lime/Shale)	8320	8480		Lime/Shale/(trace Chert)
2300	3600		Dolomite /SS (trace Shale)	8480	8600		Lime/Shale/Intermittent SS
3600	3960		Dolomite (trace SS/Anhy)	8600	8730		Shale / Limestone
3960	4030		Limestone				
4030	4100		Anhy/ Limestone / Dol				
4100	4800		Dolomite / Limestone				
4800	5150		Dolomite				
5150	6680		Limestone / Shale				
6680	7390		Lime / Shale / SS				