N.M.O.C.D. C	OLI
--------------	-----

ċ

Form 9–331 (May 1963)	UNITED STATES DEPARTMENT OF THE INTERI GEOLOGICAL SURVEY	SUBMIT IN TRIPLICATE* (Other instructions on re- verse side)	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND BERIAL NO. NM-063808		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use "APPLICATION FOR PERMIT- " for such proposals.)			RECEIVED		
1. OIL GAS WELL WELL		<i></i>	С цираря 1979 на наме		
2. NAME OF OPERATOR AR			C. C. MOR LEASE NAME ESLA STEFFE AVIS		
3. ADDRESS OF OPERAT	on	9. WELL NO.			
P. O. BOX 4. LOCATION OF WELL See also space 17 b At surface	1933, Roswell, N. M. 882 (Report location clearly and in accordance with any elow.) 1980' FNL & 1980' F	10. FIELD, AND POOL, OR WILDCAT Scuth Empire Wildcat MOrrow 11. SEC., T., R., M., OR BLK. AND SURVEY OR ABEA			
14. PERMIT NO.	15. ELEVATIONS (Show whether DF 3511.1' GI		Sec. 17, T-18S, R-29E 12. COUNTY OF PARISH 13. STATE Eddy N. M.		
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data					
	NOTICE OF INTENTION TO :		UENT REPORT OF:		
TEST WATER SHU? FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) 17. DESCRIBE PROPOSET proposed work, nent to this work	MULTIPLE COMPLETE ABANDON® CHANGE PLANS OR COMPLETED OPERATIONS (Clearly state all pertine) If well is directionally drilled, give subsurface locs	(Note: Report results Completion or Recomp	REPAIRING WELL. ALTERING CASING ABANDONMENT ⁶ A Surface & int. X CSG. s of multiple completion on Well letion Report and Log form.) , including estimated date of starting any al depths for all markers and zones perti-		
12-7-79 12-8-79 12-9-79 12-12-79	Spudded 17 1/2" hole at Depth 372'. Ran 11 join casing & set at 372' KB. PD at 6:30 pm. Cement d annulus to surface w/10 After 18 hours WOC teste Depth 2900'. Ran 65 joi 32#, ST&C new J-55 casin w/700 Sx HLW w/1/4# floc 200 Sx Cl C w/2% CaC1/Sx did not circulate. Fill cu yds Redi-mix.	ts (375.22') 13 Cemented w/375 S id not circulate. cubic yards Redi-r d casing w/600 ps nts (2902.61') 8 g and set at 2900 ele, 5# gilsonite . PD at 1:15 pm	Filled casing mix cement. i - 30 min. OK. 5/8" OD, 24# & ' KB. Cemented & 8# salt/sx and 12-11-79. Cement		
		RECEIVE			
	\frown i	DEC 1 8 1979 U.S. GEOLOGICAL SI ARTESIA, NEW ME	IRVEY		
18. I hereby certify t SIGNED	hat the foregoing is true and correct	Engineer			
(This space/fer 1	Pederal or State office use)		h: 0000		
APPROVED BY	APPROVAL, IF ANY:	<u>1947 - Britishi Sangaran</u> an	DATE373		

*See Instructions on Reverse Side