

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JAN 30 1980

O. C. D.

ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		5. State Oil & Gas Lease No.
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>18</u> RANGE <u>26</u> NMPM.		8. Farm or Lease Name Bryan "ME"
15. Elevation (Show whether DF, RT, GR, etc.) 3381'		9. Well No. 1
		10. Field and Pool, or Wildcat Und. Atoka-Yeso
		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 9½" hole at 3:00 PM 1-24-80.

TD 1108' - Ran 27 joints of 7" 20# J-55 ST&C (1111') of casing set at 1108'. 1-Guide shoe at 1108', 1-Insert Float at 1068'. Cemented w/200 sacks 50-50 III, 2% D-20 bentonite, 5#/sack D-42 Kolite, 1/4#/sack D-29 cellophane, 2% CaCl. Tailed in w/150 sacks Class "C" 2% CaCl. Cement circulated 35 sacks to surface. PD 7:30 PM 1-26-80. WOC18 hours, NU and reduced hole to 6¼". Drilled plug and tested to 600#. OK and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine J. Jorgensen</u>	TITLE <u>Geol. Secty.</u>	DATE <u>1-30-80</u>
APPROVED BY <u>W. A. Grasset</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>JAN 31 1980</u>

CONDITIONS OF APPROVAL, IF ANY: