

DISTRIBUTION		
SANTA FE	/	
FILE	/	
U.S.G.S.		
LAND OFFICE		
OPERATOR	/	

W MEXICO OIL CONSERVATION COMMISSION

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

FEB 13 1980

O. C. D.

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- <input type="checkbox"/>
Name of Operator Yates Petroleum Corporation ✓		
Address of Operator 207 South 4th Street - Artesia, NM, 88210		
Location of Well UNIT LETTER <u>F</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.		

5a. Indicate Type of Lease State <input type="checkbox"/> Fed <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Bryan "ME"
9. Well No. 1 1
10. Field and Pool, or Wildcat Und. Atoka-Yeso
12. County Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3381' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
NULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3098; PBTD 3090' - Ran 77 joints of 4½" 9.5# J-55 (3090') of casing set at 3090'. 1-Guide shoe at 3090'. Cemented w/400 sacks Class C 4/10% CFR-2, 2/10% Halad-22. PD 6:30 PM 2-5-80. Cement circulated 30 sacks to surface. WOC and tested to 1200#. OK.

WIH w/Select Fire casing gun and perforated 2664-2936' w/29 .34" holes (1 shot at each depth) as follows: 2664, 2704, 2742, 2769, 2773, 2779, 2783, 2722, 2840, 2853, 2877, 2910, 2936. (13 shots). 2700, 2716, 2732, 2753, 2766, 2771, 2777, 2781½, 2820, 2837, 2842, 2847, 2854½, 2874, 2907, 2934 (16 shots). Perforated in 2 stages. Sand Frac'd perforations w/ 60000 gallons gelled KCL and 95000# sand, 75000# 20-40 sand and 20000# 100 mesh. Broke formation w/12 bbls 15% NE HCL when perforating. Installed pumping equipment and now recovering load.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson

TITLE Geol. Secty.

DATE 2-13-80

APPROVED BY W. A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE FEB 14 1980

CONDITIONS OF APPROVAL, IF ANY: