

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved,
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 067132

6. IF INDIAN, NAME OF TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Southland Royalty Company		8. FARM OR LEASE NAME Empire Federal Com.
3. ADDRESS OF OPERATOR 1100 Wall Towers, West, Midland, Texas 79701		9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FWL, Sec. 27, T-18-S, R-29-E		10. FIELD AND POOL, OR WILDCAT Undesignated (Morrow)
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 27, T-18-S, R-29-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3459.4' GR		12. COUNTY OR PARISH Eddy
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Spud, set csg, test csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud by Hondo Drllg Co. Rig #5 @ 2:30 PM 12-20-79. Drill 15" hole to 350' 1/2" @ 305'.
 Ran 11 3/4" 42# H-40 ST&C csg set @ 350'. Cement w/ 275 sx Class "C" 2% Calcium Chloride.
 Plug down @ 1:00 PM 12-21-79. Cement circ. to surface. WOC 18 hrs. Nipple up BOP.

After 24 hrs WOC time test csg and BOP to 800# for 30 min, hole OK. Compressive
 strength of Class "C" w/2% C.C. after 24 hrs is 2275 psi @ 95° F.

Drill shead 11" hole.

RECEIVED

JAN 4 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. Harney

TITLE

District Engineer

DATE

12-27-79

(This space for Federal or State office use)

(Orig. Sgd.) GEORGE H. STEWART

ACTIVE DISTRICT ENGINEER

TITLE

DATE

JAN 04 1980

CONDITIONS OF APPROVAL, IF ANY: