

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 01159
RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

FEB 27 1980

7. UNIT AGREEMENT NAME

O. C. D.

8. FARM OR LEASE NAME

Nelson-Yates MR Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT Und.

Grayburg SA-Loce Hills ON.

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA

Sec. 3-18S-30E

Unit J NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

Co

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug well to be drilled or plugged.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

FEB 25 1980

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FSL & 1650' FEL of Section 3-18S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3524' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Prod. Csg. ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3777' - Ran 5½" 14# & 15.5# K-55 ST&C casing as follows: 77 joints 14# (3095'); 17 joints 15.5# (683') (Total 3778') of casing set at 3777'. 1-guide shoe at 3777'. Cemented w/350 sacks Howco Lite, 8#/sack salt. Followed w/325 sacks 50-50 Poz "C", 4% gel, 2/10% CFR-2, 4/10% Halad-22, 3#/sack KCL. PD 3:30 AM 2-5-80. WOC and tested to 1500# OK. Ran Temperature Survey and found top of cement at 1050.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE Geol. Secty.

DATE 2-23-80

(This space for Federal or State office use)

APPROVED BY

(Sgt. 2nd) ALBERT W. STALL

TITLE ACTING DISTRICT ENGINEER

DATE FEB 26 1980

CONDITIONS OF APPROVAL, IF ANY: