

NO. OF COPIES RECEIVED		
DISTRIBUTION		
ALBUQUERQUE	1	
EL PASO	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION **RECEIVED**

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65.

FEB 21 1980

O. C. D.

SUNDY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th Street - Artesia, NM 88210

Location of Well

UNIT LETTER E 2310 FEET FROM THE North LINE AND 990 FEET FROM

THE West LINE, SECTION 33 TOWNSHIP 18S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3385' GR

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name

Lewis "MW"

9. Well No.

1

10. Field and Pool, or Wildcat

Undes. Atoka-Yeso

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER Prod csg, perf and treat ☒

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3100'; PBTD 3081' - Ran 76 joints of 4-1/2" 9.5# J-55 ST&C (3081') of casing set at 3081'. 1-float shoe at 3081'. Cemented w/375 sacks Class "C" cement, 4/10% Flac, 2/10% Tic. PD 3:26 PM 2-15-80. Circulated 28 sacks to surface. WOC and tested to 1000#, OK.

Perforated 2733-2962' w/25 .50" holes in 2 stages as follows: 1st stage: 2733, 2755, 2787, 2996, 2812, 2830, 2847, 2868, 2895, 2916, 2928, 2959' (12 holes). Broke formation down w/1000 gallons regular acid. 2nd stage: 2745, 2783, 2791, 2794, 2805, 2815, 2838, 2856, 2876, 2925, 2933 1/2, 2941, 2962' (13 holes). Sand Frac'd perforations w/60000 gallons gelled KCL water, 95000# sand (75000# 20-40 sand & 20000# 100 mesh).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE Geological Secretary

DATE 2-20-80

APPROVED BY

TITLE SUPERVISOR, DISTRICT II

DATE FEB 22 1980

CONDITIONS OF APPROVAL, IF ANY: