

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N.M.O.C.D. COPY

SUBMIT IN TRI. DATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION **RECEIVED**
NM-020566. IF INDIAN, ALLOTTEE OR TRIBE NAME
APR 28 19807. UNIT AGREEMENT NAME
ARTESIA, OFFICE8. FARM OR LEASE NAME
NorthTurkey Track MU9. WELL NO.
1 Fed. Com10. FIELD AND POOL, OR WILDCAT
Undesignated NorthTurkey Track Morrow11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 33-18S-29E
Unit C NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3428.8 GR

12. COUNTY OR PARISH
Eddy13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set production casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 11500' - Ran 261 joints of 5½" 20# & 17# N-80 LT&C casing as follows: 12 joints 20# (498'); 248 joints 17# (10873') & 1 joint 20# (41') (Total 11412') of casing set at 11412'. Diff-fill float shoe at 11412', Diff-fill float collar at 11369'. 12 centralizers. Cemented w/425 50-50 Poz, 3/10% Halad 22, 6/10% CFR-2, 5#/sack KCL, 250 sacks Class H, 3/10% Halad-22, 6/10% CFR-2, 5#/sack KCL. PD 7:00 PM 4-9-80. 250 gallons of mud flush used ahead of cement. Ran Temperature Survey found top of cement at 8800'; WLPBTD 11372'.

TD 11500'; PBTB 11372' - WIH w/Tubing Conveyed Gun and Guiberson Uni VI packer on 2-7/8" tubing, set packer at 11169'. Perforated 11205-11230' w/56 .50" holes (4 spf) as follows: 11204-11212' (28 holes), 11223-11230' (28 holes) (56 holes). Dropped bar, GTS in 3 minutes, drilling fluid to surface in 13 minutes. Well cleaned up and flowed 640# on 1/2" choke ARO 3918 MCFPD.

18. I hereby certify that the foregoing is true and correct

SIGNED

Kristine Tomlinson

TITLE Geol. Secty.

DATE 4-24-80

(This space for Federal or State office use)

APPROVED BY

(Sgd.) GEORGE A. HAWKINS

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: