

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI. CATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-025606-5 RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MAY - 5 1980

7. UNIT AGREEMENT NAME

O. C. D.

8. FARM OR LEASE NAME, ADDRESS, OFFICE  
Rio Pecos MH Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Und. ~~Mormon~~ Red Lake Perm.11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASec. 29-18S-27E  
Unit I NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

APR 28 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FSL &amp; 1100' FEL of Section 29-18S-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3362' GR

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Spud

## SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 17½" hole at 5:00 PM 4-3-80.

TD 365' - Ran 11 joints of 13-3/8" 48# ST&amp;C (365') of casing set at 365'. Ran 1-Texas Pattern guide shoe at 365' and insert float at 335'. Cemented w/350 sacks Class C 4% CaCl. PD 10:30 PM 4-4-80. Circulated 40 sacks of cement to the surface. WOC 12 hours, backed off, reduced hole to 12¼", drilled plug and tested to 600# OK and resumed drilling.

TD 2010' - Ran 50 joints of 8-5/8" 24# LT&amp;C (2014') of casing set at 2010'. 1-guide shoe at 2010' and insert float at 1974'. Cemented w/800 sacks of 65-35 poz, 8# Kolite, 1/4# celloflake and 3% CaCl. Tailed in w/150 sacks of Class C 2% CaCl. PD 11:35 AM 4-10-80. Circulated 50 sacks of cement to the surface. WOC 18 hours, NU and tested to 1500# OK, reduced hole to 7-7/8", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Tomlinson*

TITLE

Geol. Secty.

DATE 4-26-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: