

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED</p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small></p>		<p>5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/></p> <p>5. State Oil & Gas Lease No. B-5984</p>
<p>OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/></p> <p>1. Name of Operator Holly Energy Inc.</p> <p>2. Address of Operator Box 726 Artesia, N.M.</p> <p>3. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>840</u> FEET FROM <u>East</u> THE <u>30</u> LINE, SECTION <u>17 S</u> TOWNSHIP <u>28 E</u> RANGE <u>30</u> N.M.P.M.</p>		<p>7. Unit Agreement Name</p> <p>8. Farm or Lease Name State 30 Co m</p> <p>9. Well No. 1</p> <p>10. Field and Pool, or Wildcat Empire Penn</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 3565.4 Gr</p>		<p>12. County Eddy</p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well 2-26-80 set 423' 13^{3/8} 48# casing, cement with 260 sx 50/50 pos
4% Bentonite 2% cacl. 100 sx class C 2% cacl. circulated 25 sx to pit-2-27-80
after waiting 18 hrs. drill 11" hole to 1994' set 1992' 8^{5/8} 24# casing cement
with 500 sx 50/50 pos 2% Bentonite 5# Kolite, 1/4 # celophane flakes per sx
200 sx class C 2% cacl. circulated 30 sx to pit 3-2-80 after waiting 18 hours
drill out with bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Robert Lloyd TITLE District Supt. DATE 3-5-80

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: