

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Galea Petr. Corp.</u>		Lease <u>Danell MV</u>		Well # <u>2</u>	
Location of Well	Unit <u>16505</u> <u>1650E</u>	Section <u>33</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>Cactus Drilling Co.</u>	Type of Equipment <u>Rotary to start soon</u> <u>Approved 2-6-80</u>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>9 1/2"</u>	<u>7"</u>	<u>20</u>	<u>20</u>	<u>1120</u>	<u>550 cts.</u>
<u>6 1/4"</u>	<u>4 1/2"</u>	<u>9.5</u>		<u>3100</u>	<u>275 cts.</u>

Casing Data:

Surface 27 joints of 7 inch 20 # Grade J-55
☒ (Approved) ☐ (Rejected)

Inspected by MW date 2/24/80

Cementing Program

Size of hole 9 1/2" Size of Casing 7 Sacks cement required 350 sy

Type of Shoe used Guide Float collar used Inset Btm 3 jts welded Yes

TD of hole 1110 Set 140 Feet of 7 Inch 20 # Grade J-55

New-used csg. @ 1088 with 150 sacks neat cement around shoe

+ 200 sax 65/35 P-2 additives 426-1-1/4" (110) P-2 - 5# K-101 - 2710

Plug down @ 10:20 (AM) (PM) Date 2/24/80

Cement circulated Yes No. of Sacks 20

Cemented by Danell Witnessed by MW

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Block 1010-1015